


SPECIFICATION SHEET

a

WALL **CONTROLS**




Model CD60W (White) 20-40-60 Minute Countdown Timer

- Fits single-gang box
- 120 VAC, 9 Amp Max.
- For use with all Broan fans within Amp rating



Model MS100W (White) **Occupancy Sensor**

- Fits single-gang box
- LED/CFL 300W, Incandescent 600W, 1/2 HP, 120 VAC, 9 Amp Max. (Fan + Light)
- · For use with all Broan fans within Amp rating



Model DD500W (White) **Digital Dehumidistat**

- Fits single-gang box120 VAC, 9 Amp Max.

Model DT100W (White) **Delay Off Timer**

• Fits single-gang box

Amp rating

• 120 VAC, 6 Amp Max.

(3 A Fan + 3 A Lamp)

• For use with all Broan fans within

• For use with all Broan fans within Amp rating



Model P2RW (White) 2 Rocker Switch

- Two, independent, 120 VAC, 15 Amp rocker switches
- Can be used in a 15 amp or 20 amp branch circuit
- Fits single-gang box For use with all Broan fans and • heaters within Amp rating

Model P3RW (White) 3 Rocker Switch

- Three, independent, 120 VAC, 15 Amp rocker switches
- Can be used in a 15 amp or 20 amp • branch circuit
- Fits single-gang box For use with all Broan fans and • heaters within Amp rating



0

Model SC100W (White) Speed Control

- Fits single-gang box
- 120 VAC, 3 Amp Max.
- For use only with Broan fans that can be used with speed controls and within Amp rating

Broan Hartford, Wisconsin www.broan.com 800-558-1711				
BIOAN HAILIOID, WISCONSIN WWW.DIOAN.COM 600-556-1711	Broan	Hartford, Wisconsin	www.broan.com	800-558-1711

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date







69W (White)

Single-Function Control

- Fits single-gang box
 120 VAC, 15 Amp
 For use with all Broan fans within Amp rating



Model 80L

Electronic Speed Control (Internal)

- Specially designed for use with Broan LoSone Select[®] ventilators rated at 3 Amps or less
- Metal housing
- 3 A, 120 VAC, 60 Hz

Model 71V (Ivory) 12-Hour Timer

- · Operates continuously or for any set period up to 12 hours
- Fits single-gang box 120 VAC, 20 Amp or 240 VAC, 10 • Amp capacity
- For use with all Broan fans and heaters within Amp rating



Model 72V (Ivory), 72W (White) Electronic Variable Speed Control (6 Amp)

- Rotary dial for variable selection of fan speed and sound level
- . Positive on/off action
- Fits single-gang box •
- Built-in radio noise suppressor
- Switched wire included for additional use if desired (120 VAC, 6 Amp)
- For use with all Broan fans within
- Amp rating except ceiling paddle fans Do not use with impedance protected motor

Model 75V (Ivory) Electronic Variable Speed Control (6 Amp) • 240 VAC, 6 Amp capacity

- For use with Broan Model L3500EXL LoSone[®] Select[™] Cabinet Ventilator
- Other features same as Model 72V




Model 77DV (Ivory), 77DW (White) **Four-Function Control**

- Specially designed for use with Broan SensAire® and Designer Series fan/ lights
- Separate switches control fan (on/off/ ٠ auto), light (on/off), and night-light (on/ off)
- 120 VAC, Amps each rocker = 15, 15, 5 (20 Amp total)
- Fits single-gang opening
- Includes switch function labels

Model 82W (White), 82A (Light Almond)

- Premium Humidity Sensing Wall Control
 Sensaire™ technology detects rising humidity to react to showers and clear mirrors quickly
- Variable setting from 20% to 80% relative humidity
- Can be used to comply with California Title 24 and CALGreen
- Precise sensitivity adjustment
- · Continuous ventilation mode operates fan set minutes per hour to meet ASHRAE 62.2
- User-adjustable automatic shutoff timer
- LED indicator and manual operation mode
- Fits single-gang box
- 120 VAČ, 60 Hž
- Requires neutral wire for operation.



 \mathbf{D}

Model 269VL (Ivory), 269WL (White) Two-Function Control with Indicator

- Red light indicates power is on
- Specially designed for use with Broan Solitaire® Ultra Silent[™] fans and an auxiliary light source
- Fits two-gang box 120 VAC, 20 Amp lighted switch; 120/240/277 VAC, 15 Amp unlighted switch



- Three-Function Control with Indicator
- Specially designed for use with Broan Solitaire[®] Ultra Silent[™] fans /lights
- Fits two-gang box 120 VAC, 20 Amp lighted switch; 120 VAC, 15 Amp each unlighted switch (20 Amp total)

Model DH100W Dehumidistat

- Fits single-gang box
- Variable setting from 20% to 80% relative humidity
 Dual voltage (24V/120V)
- Usage guide included





Model 57V (Ivory), 57W (White)

Electronic Variable Speed Control (3 Amp) Rotary dial for variable selection of fan spéed and sound level

- Positive off position •
- Fits single-gang box

•

.

- Built-in radio noise suppressor
- 120 VAC, 3.0 Amp capacity
- For use with all Broan fans within Amp rating • except ceiling paddle fans
- Do not use with impedance protected motor •

Model 59V (Ivory), 59W (White) 60-Minute Time Control

- Operates continuously or for any set period up to 60 minutes
- Fits single-gang box •
- 120 VAČ, 20 Amp or 240 VAC, 10 Amp capacity
- Also recommended for low voltage (30V Max) • applications
- For use with all Broan fans and heaters within • Amp rating

Model 61V (Ivory), 61W (White) 15-Minute Time Control

- Operates for any set period up to 15 minutes (no "continuous on" position)
- Fits single-gang box
- 120 VAČ, 20 Amp or 240 VAC, 10 Amp capacity Also recommended for low voltage (30V Max) applications
- For use with all Broan fans and heaters within • Amp rating

Model 62W (White) 60-Minute Time Control with Two Rocker Switches

- Two, independent, 120 VAC, 15 Amp rocker switches (20 Amp Total)
- Timer operates continuously or for any set period up to 60 minutes
- Fits two-gang box
- 120 VAC, 20 Amp or 240 VAC, 10 Amp timer capacity
- For use with all Broan fans and heaters within Amp rating





Model 63V (Ivory), 63W (White)

- 60-Minute Time Control with Rocker Switch One, independent 120 VAC, 15 Amp rocker switch
- Timer has same features as Model 62V/62W
- For use with all Broan fans and heaters within • Amp rating

Model 64V (Ivory), 64W (White) Fan/Light Control with Off-Delay

- Fan and light operate together when control is turned on. Fan continues to operate for a set time period (user adjustable from 1-60 minutes) after light is turned off
- Center position turns fan and light off immedi-• ately
- Can also be used with a fan only
- •
- Fits single-gang box 120 VAC, 4 Amp (fan) and 4 Amp (light) capac-ity
- For use with all Broan fans and fan/lights within . Amp rating. Requires both sides of the electrical line (hot & neutral) in the switchbox

Model 66V (Ivory), 66W (White) Three-Function Control with Plastic Wall Plate

Model 67W (White) Three-Function Control with Chrome Finish Metal Wall Plate

- Three, independent, 120 VAC, 15 Amp rocker switches (20 Amp total)
- •
- Fits single-gang opening For use with all Broan fans and heaters within Amp rating

Model 68V (Ivory), 68W (White) **Two-Function Control**

- Two, independent, 120 VAC, 15 Amp rocker switches (20 Amp total)
- Fits single-gang box
- For use with all Broan fans and heaters within • Amp rating

For more information on compatibility with Broan and NuTone fans, refer to the wall control selection guide on Broan-NuTone.com.

